

1. Identification

| | | |
|---|---|----------------|
| Product identifier | Crude Oil Sour (West Texas Intermediate) | |
| Other means of identification | Not available. | |
| Recommended use | Fuel | |
| Recommended restrictions | None known. | |
| Manufacturer/Importer/Supplier/Distributor information | | |
| Company name | Noble Energy, Inc. | |
| Address | 1001 Noble Energy Way Houston, TX 77070 US US | |
| Telephone | Non-emergency Telephone: | 720-587-2085 |
| E-mail | SDSGLOBAL@nobleenergyinc.com | |
| | | |
| Emergency phone number | 24 Hour Emergency: | 1-760-476-3962 |
| | Access code | 333053 |

2. Hazard(s) identification

| | | |
|------------------------------|--|--|
| Physical hazards | Flammable Liquids | Category 2 |
| Health Hazards | Acute toxicity, inhalation | Category 2 |
| | Serious eye damage/eye irritation | Category 2A |
| | Germ cell mutagenicity | Category 1B |
| | Carcinogenicity | Category 1A |
| | Reproductive toxicity | Category 2 |
| | Specific Target Organ Toxicity, Single Exposure | Category 3 narcotic effects |
| | Specific Target Organ Toxicity, Repeated Exposure | Category 1 (Blood, Central nervous system) |
| | Aspiration hazard | Category 1 |
| Environmental hazards | Hazardous to the aquatic environment, acute hazard | Category 2 |
| | Hazardous to the aquatic environment, long-term hazard | Category 2 |
| OSHA defined hazards | Not classified. | |
| Label elements | | |



Signal word

Danger

Hazard statement

Highly flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. Fatal if inhaled. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs (Blood, Central nervous system) through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects. Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment.

Precautionary statement

Prevention

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Do not breathe gas. Use only outdoors or in a well-ventilated area. Avoid release to the environment.

Response

If swallowed: Immediately call a poison center/doctor/. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Take off contaminated clothing and wash before reuse. If skin irritation occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center/doctor. Collect spillage.

Storage

Store in a well-ventilated place. Keep cool. Store locked up. Keep container tightly closed.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

Static accumulating flammable liquids

3. Composition/information on ingredients

Mixtures

| Chemical name | CAS number | % |
|----------------------|------------|-------|
| Petroleum distillate | 8002-05-9 | > 95 |
| n-Hexane | 110-54-3 | 4 - 7 |
| Hydrogen sulfide | 7783-06-4 | 1 - 3 |
| Benzene | 71-43-2 | 0 - 2 |
| Toluene | 108-88-3 | 0 - 2 |
| Ethylbenzene | 100-41-4 | 0 - 1 |
| Xylene | 1330-20-7 | 0 - 1 |

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation

Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

Skin contact

Wash skin with soap and water. Get medical attention promptly if symptoms occur after washing.

Eye contact

Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. Get medical attention if symptoms persist.

Ingestion

Call a physician or poison control center immediately. DO NOT induce vomiting. If victim is fully conscious, give a cupful of water. Never give anything by mouth to an unconscious person. If vomiting occurs, keep head lower than the hips to help prevent aspiration.

Most important symptoms/effects, acute and delayed

Fatal if inhaled. May cause genetic defects. Suspected of damaging fertility or the unborn child. Causes damage to organs (Blood, Central nervous system) through prolonged or repeated exposure. Skin and eye irritation. Vapors may cause drowsiness and dizziness. Swallowing of the liquid, or vomiting as a result, may result in aspiration into the lungs. May contain poisonous and flammable hydrogen sulfide vapor in container headspace. Odor does not provide a reliable indicator of the presence of hazardous levels in the atmosphere. In high concentrations (500-1000 ppm), H₂S acts as a systemic poison causing unconsciousness and death.

Indication of immediate medical attention and special treatment needed

Treat symptomatically. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficulty breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

| | |
|--|--|
| Suitable extinguishing media | Foam. Dry chemical powder. Carbon dioxide (CO ₂). Water fog. |
| Unsuitable extinguishing media | Do not use a solid water stream as it may scatter and spread fire. |
| Specific hazards arising from the chemical | Containers may explode when heated. Thermal decomposition or combustion may liberate toxic gases or fumes. May contain harmful concentrations of hydrogen sulfide, which can accumulate in the head space. |
| Special protective equipment and precautions for firefighters | Self-contained breathing apparatus and full protective clothing must be worn in case of fire. |
| Specific methods | Move container from fire area if it can be done without risk. Use water spray to keep fire-exposed containers cool. |

6. Accidental release measures

| | |
|--|---|
| Personal precautions, protective equipment and emergency procedures | Eliminate sources of ignition. Wear appropriate personal protective equipment (See Section 8). Before entering storage tanks and commencing any operation in a confined area, check the atmosphere for oxygen content, hydrogen sulfide (H ₂ S) and flammability. |
| Methods and materials for containment and cleaning up | Eliminate sources of ignition. Absorb spill with vermiculite or other inert material, then place in a container for chemical waste for proper disposal. Large Spills: Use water spray to disperse vapors and dilute spill to a nonflammable mixture. Prevent runoff from entering drains, sewers, or streams. Dike for later disposal. |
| Environmental precautions | Avoid discharge into drains, water courses or onto the ground. |

7. Handling and storage

| | |
|---|---|
| Precautions for safe handling | Keep away from heat, sparks and open flame. Do not breathe gas. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. Use only with adequate ventilation. May contain poisonous and flammable hydrogen sulfide vapor in container headspace. |
| Conditions for safe storage, including any incompatibilities | Keep container tightly closed and in a well-ventilated place. Store away from incompatible materials. Before entering storage tanks and commencing any operation in a confined area, check the atmosphere for oxygen content, hydrogen sulfide (H ₂ S) and flammability. |

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

| Components | Type | Value |
|-----------------------|------|-------|
| Benzene (CAS 71-43-2) | STEL | 5 ppm |
| | TWA | 1 ppm |

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | Value |
|-----------------------------|------|------------------------|
| Ethylbenzene (CAS 100-41-4) | PEL | 435 mg/m ³ |
| | | 100 ppm |
| n-Hexane (CAS 110-54-3) | PEL | 1800 mg/m ³ |
| | | 500 ppm |

US. OSHA Table Z-2 (29 CFR 1910.1000)

| Components | Type | Value |
|----------------------------------|---------|---------|
| Benzene (CAS 71-43-2) | Ceiling | 25 ppm |
| | TWA | 10 ppm |
| Hydrogen sulfide (CAS 7783-06-4) | Ceiling | 20 ppm |
| | | 300 ppm |
| Toluene (CAS 108-88-3) | Ceiling | 300 ppm |
| | TWA | 200 ppm |

US. ACGIH Threshold Limit Values

| Components | Type | Value |
|-----------------------|------|---------|
| Benzene (CAS 71-43-2) | STEL | 2.5 ppm |
| | TWA | 0.5 ppm |

US. ACGIH Threshold Limit Values

| Components | Type | Value |
|----------------------------------|------|--------|
| Ethylbenzene (CAS 100-41-4) | TWA | 20 ppm |
| Hydrogen sulfide (CAS 7783-06-4) | STEL | 5 ppm |
| | TWA | 1 ppm |
| n-Hexane (CAS 110-54-3) | TWA | 50 ppm |
| Toluene (CAS 108-88-3) | TWA | 20 ppm |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value |
|--------------------------------------|---------|------------|
| Benzene (CAS 71-43-2) | STEL | 1 ppm |
| | TWA | 0.1 ppm |
| Ethylbenzene (CAS 100-41-4) | STEL | 545 mg/m3 |
| | | 125 ppm |
| | TWA | 435 mg/m3 |
| Hydrogen sulfide (CAS 7783-06-4) | | 100 ppm |
| | Ceiling | 15 mg/m3 |
| n-Hexane (CAS 110-54-3) | | 10 ppm |
| | TWA | 180 mg/m3 |
| | | 50 ppm |
| Petroleum distillate (CAS 8002-05-9) | Ceiling | 1800 mg/m3 |
| | | |
| Toluene (CAS 108-88-3) | TWA | 350 mg/m3 |
| | STEL | 560 mg/m3 |
| | | 150 ppm |
| | TWA | 375 mg/m3 |
| | | 100 ppm |

Biological limit values

ACGIH Biological Exposure Indices

| Components | Value | Determinant | Specimen | Sampling Time |
|-----------------------------|-----------|---|---------------------|---------------|
| Benzene (CAS 71-43-2) | 25 µg/g | S-Phenylmercapturic acid | Creatinine in urine | * |
| | 25 µg/g | S-Phenyl-mercapturic acid | | * |
| Ethylbenzene (CAS 100-41-4) | 0.15 g/g | Sum of mandelic acid and phenylglyoxylic acid | Creatinine in urine | * |
| n-Hexane (CAS 110-54-3) | 0.4 mg/l | 2,5-Hexanedione, without hydrolysis | Urine | * |
| | 0.4 mg/l | 2,5-Hexanedione, without hydrolysis | | * |
| Toluene (CAS 108-88-3) | 0.3 mg/g | o-Cresol, with hydrolysis | Creatinine in urine | * |
| | 0.03 mg/l | Toluene | Urine | * |
| | 0.02 mg/l | Toluene | Blood | * |

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

| | |
|-------------------------|-----------------------------------|
| Benzene (CAS 71-43-2) | Can be absorbed through the skin. |
| n-Hexane (CAS 110-54-3) | Can be absorbed through the skin. |
| Toluene (CAS 108-88-3) | Can be absorbed through the skin. |

US - Minnesota Haz Subs: Skin designation applies

Toluene (CAS 108-88-3)

Skin designation applies.

US ACGIH Threshold Limit Values: Skin designation

Benzene (CAS 71-43-2)

Can be absorbed through the skin.

n-Hexane (CAS 110-54-3)

Can be absorbed through the skin.

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas. Provide easy access to water supply and eye wash facilities.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Wear safety glasses with side shields (or goggles).

Skin protection**Hand protection**

Chemical resistant gloves are recommended.

Other

Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Respiratory protection

Hydrogen sulfide impairs olfactory nerve function above 20 ppm, odor warning property (rotten egg smell) lost at higher concentrations.

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Respirator type: Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister.

Thermal hazards

Not applicable.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties**Appearance**

Liquid.

Physical state

Liquid.

Form

Liquid.

Color

Black.

Odor

Hydrocarbon-like.

Odor threshold

Not relevant.

pH

Not relevant.

Melting point/freezing point

-7.6 °F (-22 °C)

Initial boiling point and boiling range

132.8 °F (56 °C) at 1 atmosphere

Flash point

14.0 °F (-10.0 °C) Pensky-Martens Closed Cup

Evaporation rate

2.6 (n-Butylacetate=1)

Flammability (solid, gas)

Not relevant.

Upper/lower flammability or explosive limits**Flammability limit - lower (%)**

1

Flammability limit - upper (%)

7

Vapor pressure

8.6 (atmosphere) at 38°C

Vapor density

0.67 at 20°C/60°F

Relative density

0.867

Relative density temperature

59 °F (15 °C)

Solubility(ies)**Solubility (water)**

52 mg/l Soluble

Partition coefficient (n-octanol/water)

5

Auto-ignition temperature

437 °F (225 °C)

Decomposition temperature

Not relevant.

Viscosity

4.99 cSt at 40°C

| | |
|-----------------------|------------------------|
| | 5.24 cSt at 60°C |
| Viscosity temperature | 140 °F (60 °C) |
| Other information | API Gravity 36 at 60°F |
| Bulk density | 6 lb/gal |
| VOC (Weight %) | 2.7 % |

10. Stability and reactivity

| | |
|------------------------------------|---|
| Reactivity | The product is stable and non-reactive under normal conditions of use, storage and transport. |
| Chemical stability | Material is stable under normal conditions. |
| Possibility of hazardous reactions | Hazardous polymerization does not occur. |
| Conditions to avoid | Keep away from heat, sparks, and flame. |
| Incompatible materials | Strong oxidizing agents. |
| Hazardous decomposition products | No hazardous decomposition products are known. |

11. Toxicological information

Information on likely routes of exposure

| | |
|--------------|---|
| Inhalation | Fatal if inhaled. May cause drowsiness or dizziness. |
| Skin contact | Causes skin irritation. |
| Eye contact | Causes serious eye irritation. |
| Ingestion | Swallowing or vomiting of the liquid may result in aspiration into the lungs. |

| | |
|--|---|
| Symptoms related to the physical, chemical and toxicological characteristics | Fatal if inhaled. Swallowing or vomiting of the liquid may result in aspiration into the lungs. Skin and eye irritation. Vapors may cause drowsiness and dizziness. Causes damage to organs (Blood, Central Nervous System) through prolonged or repeated exposure. Hydrogen sulfide impairs olfactory nerve function above 20 ppm, odor warning property (rotten egg smell) lost at higher concentrations. |
|--|---|

Information on toxicological effects

| | |
|----------------|---|
| Acute toxicity | Fatal if inhaled. May be fatal if swallowed and enters airways. |
|----------------|---|

| Components | Species | Test Results |
|----------------------------------|---------|--------------------------------------|
| Benzene (CAS 71-43-2) | | |
| Acute | | |
| <i>Oral</i> | | |
| LD50 | Mouse | 4700 mg/kg |
| | Rat | 3306 mg/kg |
| Ethylbenzene (CAS 100-41-4) | | |
| Acute | | |
| <i>Dermal</i> | | |
| LD50 | Rabbit | > 5000 mg/kg 17.8 ml/kg, 24 Hours |
| <i>Inhalation</i> | | |
| LC50 | Mouse | > 8000 ppm, 20 Minutes |
| | Rat | 4000 ppm |
| <i>Oral</i> | | |
| LD50 | Rat | 5.46 g/kg |
| <i>Other</i> | | |
| LD50 | Mouse | 17.81 mm/kg |
| Hydrogen sulfide (CAS 7783-06-4) | | |
| Acute | | |
| <i>Inhalation</i> | | |
| LC50 | Rat | > 0.38 mg/l, 960 Minutes |

| Components | Species | Test Results |
|---|---|-----------------------------------|
| n-Hexane (CAS 110-54-3) | | |
| Acute | | |
| <i>Dermal</i> | | |
| LD50 | Rabbit | > 2 g/kg |
| <i>Oral</i> | | |
| LD50 | Rat | 28710 mg/kg |
| Toluene (CAS 108-88-3) | | |
| Acute | | |
| <i>Dermal</i> | | |
| LD50 | Rabbit | 14.1 ml/kg |
| <i>Inhalation</i> | | |
| LC50 | Rat | 49000 mg/m ³ , 4 Hours |
| <i>Oral</i> | | |
| LD50 | Rat | 636 mg/kg |
| Skin corrosion/irritation | Causes skin irritation. | |
| Serious eye damage/eye irritation | Causes serious eye irritation. | |
| Respiratory or skin sensitization | | |
| Respiratory sensitization | Not a respiratory sensitizer. | |
| Skin sensitization | Not a skin sensitizer. | |
| Germ cell mutagenicity | May cause genetic defects. | |
| Carcinogenicity | May cause cancer. | |
| IARC Monographs. Overall Evaluation of Carcinogenicity | | |
| Benzene (CAS 71-43-2) | 1 Carcinogenic to humans. | |
| Ethylbenzene (CAS 100-41-4) | 2B Possibly carcinogenic to humans. | |
| Petroleum distillate (CAS 8002-05-9) | 3 Not classifiable as to carcinogenicity to humans. | |
| Toluene (CAS 108-88-3) | 3 Not classifiable as to carcinogenicity to humans. | |
| NTP Report on Carcinogens | | |
| Benzene (CAS 71-43-2) | Known To Be Human Carcinogen. | |
| OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) | | |
| Benzene (CAS 71-43-2) | Cancer | |
| Reproductive toxicity | Suspected of damaging fertility or the unborn child. | |
| Specific target organ toxicity - single exposure | May cause drowsiness or dizziness. | |
| Specific target organ toxicity - repeated exposure | Causes damage to organs (Blood, Central nervous system) through prolonged or repeated exposure. | |
| Aspiration hazard | May be fatal if swallowed and enters airways. | |

12. Ecological information

Ecotoxicity Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

| Components | Species | Test Results |
|-----------------------------|---------|---|
| Benzene (CAS 71-43-2) | | |
| Aquatic | | |
| Crustacea | EC50 | Water flea (Daphnia magna) |
| | | 8.76 - 15.6 mg/l, 48 hours |
| Fish | LC50 | Rainbow trout,donaldson trout (Oncorhynchus mykiss) |
| | | 5.3 mg/l, 96 hours |
| Ethylbenzene (CAS 100-41-4) | | |
| Aquatic | | |
| Crustacea | EC50 | Water flea (Daphnia magna) |
| | | 1 - 4 mg/l, 48 hours |
| Fish | LC50 | Rainbow trout,donaldson trout (Oncorhynchus mykiss) |
| | | 4 mg/l, 96 hours |

| Components | Species | Test Results |
|--------------------------------------|---------|--|
| Hydrogen sulfide (CAS 7783-06-4) | | |
| Aquatic | | |
| Fish | LC50 | Lake whitefish (<i>Coregonus clupeaformis</i>) 0.002 mg/l, 96 hours |
| n-Hexane (CAS 110-54-3) | | |
| Aquatic | | |
| Fish | LC50 | Fathead minnow (<i>Pimephales promelas</i>) 2.101 - 2.981 mg/l, 96 hours |
| Petroleum distillate (CAS 8002-05-9) | | |
| Aquatic | | |
| Fish | LC50 | Cutthroat trout (<i>Oncorhynchus clarki</i>) 2.1 - 4.3 mg/l, 96 hours |
| Toluene (CAS 108-88-3) | | |
| Aquatic | | |
| Crustacea | EC50 | Water flea (<i>Daphnia magna</i>) 5.46 - 9.83 mg/l, 48 hours |
| Fish | LC50 | Rainbow trout, donaldson trout (<i>Oncorhynchus mykiss</i>) 5.89 - 7.81 mg/l, 96 hours |

Persistence and degradability Not established.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

| | |
|--|------|
| Crude Oil Sour (West Texas Intermediate) (CAS Mixture) | 4.5 |
| | 5 |
| Benzene (CAS 71-43-2) | 2.13 |
| Ethylbenzene (CAS 100-41-4) | 3.15 |
| Toluene (CAS 108-88-3) | 2.73 |
| n-Hexane (CAS 110-54-3) | 3.9 |

Mobility in soil Not available.

Other adverse effects Not established.

13. Disposal considerations

Disposal instructions Do not discharge into drains, water courses or onto the ground. Discharge, treatment, or disposal may be subject to national, state, or local laws.

Hazardous waste code D001: Waste Flammable material with a flash point <140 °F

US RCRA Hazardous Waste U List: Reference

| | |
|----------------------------------|------|
| Benzene (CAS 71-43-2) | U019 |
| Hydrogen sulfide (CAS 7783-06-4) | U135 |
| Toluene (CAS 108-88-3) | U220 |

Waste from residues / unused products Dispose of in accordance with local regulations.

Contaminated packaging Since emptied containers retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

| | |
|-------------------------------------|-----------------------------|
| UN number | UN1267 |
| UN proper shipping name | Petroleum crude oil |
| Transport hazard class(es) | |
| Class | 3 |
| Subsidiary risk | - |
| Label(s) | 3 |
| Packing group | II |
| Environmental hazards | |
| Marine pollutant | Yes |
| Special precautions for user | Not available. |
| Special provisions | 144, 357, IB2, T4, TP1, TP8 |
| Packaging exceptions | 150 |
| Packaging non bulk | 202 |
| Packaging bulk | 242 |

IATA

UN number UN1267
UN proper shipping name Petroleum crude oil
Transport hazard class(es)
Class 3
Subsidiary risk -
Packing group II
Environmental hazards Yes
ERG Code 3L
Special precautions for user Not available.

IMDG

UN number UN1267
UN proper shipping name PETROLEUM CRUDE OIL
Transport hazard class(es)
Class 3
Subsidiary risk -
Packing group II
Environmental hazards
Marine pollutant Yes
EmS F-E, S-E
Special precautions for user Not available.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code This substance/mixture is not intended to be transported in bulk.

| |
|-----------------------------------|
| 15. Regulatory information |
|-----------------------------------|

US federal regulations This product is hazardous according to OSHA 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Benzene (CAS 71-43-2) Cancer
 Central nervous system
 Blood
 Aspiration
 Skin
 Eye
 respiratory tract irritation
 Flammability

CERCLA Hazardous Substance List (40 CFR 302.4)

Benzene (CAS 71-43-2) LISTED
 Ethylbenzene (CAS 100-41-4) LISTED
 Hydrogen sulfide (CAS 7783-06-4) LISTED
 n-Hexane (CAS 110-54-3) LISTED
 Toluene (CAS 108-88-3) LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
 Delayed Hazard - Yes
 Fire Hazard - Yes
 Pressure Hazard - No
 Reactivity Hazard - No

SARA 302 Extremely hazardous substance

| Chemical name | CAS number | Reportable quantity | Threshold planning quantity | Threshold planning quantity, lower value | Threshold planning quantity, upper value |
|------------------|------------|---------------------|-----------------------------|--|--|
| Hydrogen sulfide | 7783-06-4 | 100 | 500 lbs | | |

SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)

| Chemical name | CAS number | % by wt. |
|----------------------|------------|----------|
| Petroleum distillate | 8002-05-9 | > 95 |
| n-Hexane | 110-54-3 | 4 - 7 |
| Hydrogen sulfide | 7783-06-4 | 1 - 3 |
| Benzene | 71-43-2 | 0 - 2 |
| Toluene | 108-88-3 | 0 - 2 |
| Ethylbenzene | 100-41-4 | 0 - 1 |

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Benzene (CAS 71-43-2)
 Ethylbenzene (CAS 100-41-4)
 n-Hexane (CAS 110-54-3)
 Petroleum distillate (CAS 8002-05-9)
 Toluene (CAS 108-88-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Hydrogen sulfide (CAS 7783-06-4)

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Toluene (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Toluene (CAS 108-88-3) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Toluene (CAS 108-88-3) 594

US state regulations WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

US. Massachusetts RTK - Substance List

Benzene (CAS 71-43-2)
 Ethylbenzene (CAS 100-41-4)
 Hydrogen sulfide (CAS 7783-06-4)
 n-Hexane (CAS 110-54-3)
 Petroleum distillate (CAS 8002-05-9)
 Toluene (CAS 108-88-3)

US. New Jersey Worker and Community Right-to-Know Act

Benzene (CAS 71-43-2)
 Ethylbenzene (CAS 100-41-4)
 Hydrogen sulfide (CAS 7783-06-4)
 n-Hexane (CAS 110-54-3)
 Petroleum distillate (CAS 8002-05-9)
 Toluene (CAS 108-88-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Benzene (CAS 71-43-2)
 Ethylbenzene (CAS 100-41-4)
 Hydrogen sulfide (CAS 7783-06-4)
 n-Hexane (CAS 110-54-3)
 Petroleum distillate (CAS 8002-05-9)
 Toluene (CAS 108-88-3)

US. Rhode Island RTK

Benzene (CAS 71-43-2)
 Ethylbenzene (CAS 100-41-4)
 Hydrogen sulfide (CAS 7783-06-4)
 n-Hexane (CAS 110-54-3)
 Toluene (CAS 108-88-3)

US. California Proposition 65**US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance**

Benzene (CAS 71-43-2)
 Ethylbenzene (CAS 100-41-4)
 Toluene (CAS 108-88-3)

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|--|------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | Yes |
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | Yes |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | No |
| Korea | Existing Chemicals List (ECL) | Yes |
| New Zealand | New Zealand Inventory | Yes |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | Yes |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 03-September-2014

Revision date -

Version # 01

NFPA ratings



References

ECHA registered substances database
HSDB® - Hazardous Substances Data Bank
IARC Monographs. Overall Evaluation of Carcinogenicity
National Toxicology Program (NTP) Report on Carcinogens
Registry of Toxic Effects of Chemical Substances (RTECS)

Disclaimer

The information provided herein is believed to be accurate as of the date of issue, but is offered without guarantee. The information provided may not be complete, as it is not practicable to provide all scientific information in the format of this document. Further, additional information may be necessary under exceptional conditions of use, or because of applicable laws or regulations. Noble Energy, Inc. does not assume any liability arising out of product use even if safety procedures are followed as outlined herein. The user has the responsibility for evaluating the adequacy of the information under the conditions of use and obtaining additional information where uncertainty exists. No express or implied guarantees are made as to the effects of use, the results to be obtained, or the safety and toxicity of the product in any specific application. The user assumes all risks of use of the product. Noble Energy, Inc. expressly disclaims all warranties of every kind including warranties of merchantability and fitness for any particular purpose. Nothing herein is intended to be construed as permission or recommendation for use of the product in any manner which might infringe existing patents.